



Industrial Ethernet


PoE Capability, High-performance Industrial
Automation and IIoT Solution

Total Industrial Networking Solution

PLANET Industrial Networking solution based on Industrial Ethernet, Industrial Automation and IIoT is highly-reliable and secure to ensure continuous operation in harsh environments such as factories, outdoors, and places where extreme temperatures are experienced. With industrial-grade certifications such as RoHS, CE, FCC, EN50155 and E-Mark, PLANET provides a complete product portfolio for a variety of Industrial Applications such as factory automation, intelligent transportation system and more.

Highway

Meeting EN50155 and E-Mark standards to withstand vibration, shock, etc.




Railway Transmission System

EN50155 certified equipment to ensure transmission quality





On the Train



On the Platform



Trackside Control Cabinet





Remote Control Center

- 100BASE-TX UTP
- 100BASE-TX UTP with PoE
- 100BASE-T UTP
- 100BASE-T UTP with PoE
- 1000BASE-SX/LX Fiber Optic
- 4G LTE
- 5GHz 802.11ac
- 2.4GHz 802.11n


In-Vehicle Networking

4G/LTE/GPS connectivity brings security, communications and service management in a moving vehicle.



Industrial Automation

Designed for reliable, secure and smart industrial network Infrastructures for factory automation



19" Rackmount Managed Ethernet Switches



	L3				L2+ Ring	
Model	IGS-6325-20T4C4X	IGS-6325-20S4C4X	IGS-6325-24P4X	IGS-6325-24P4S	IGSW-24040T	IGS-5225-16T4S

Product Image



Modbus TCP



Modbus TCP



Modbus TCP PoE



Modbus TCP PoE



Modbus TCP



Modbus TCP

Hardware	10/100/1000BASE-T	24	4 (Combo)	24	24	24	16
	10/100BASE-TX	-	-	-	-	-	-
	1000 mini-GBIC	4 (Combo)	24	4	4	4 (Combo)	4
	100BASE-FX	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible
	10G SFP+ Slot	4 (1000X/2500X Compatible)			-	-	-
	Switch Fabric	128Gbps	128Gbps	128Gbps	48Gbps	48Gbps	40Gbps
DI & DO	2 DI & DO	2 DI & DO	2 DI & DO	2 DI & DO	2 DI & DO	2 DI & DO	
Power	Inputs	Dual 24-60V DC 100-240V AC		Dual 48-56V DC		Dual 36-60V DC 100-240V AC	
	Connector	6-pin terminal block, AC socket		6-pin terminal block, AC socket		6-pin terminal block, AC socket	
	Consumption	42.7 watts	45 watts	500 watts	500 watts	30 watts	15.2 watts
Mechanical	Dimensions (W x D x H)	440 x 200 x 44.5 mm		440 x 300 x 44.5 mm		440 x 200 x 44.5 mm	
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	Rackmount	Rackmount	Rackmount	Rackmount	Rackmount	Rackmount
Environment	Operating Temperature	-40-75 degrees C		-40-75 degrees C		-40-75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE EN 61000-6-2	FCC Class A, CE EN 61000-6-2 EN 61000-6-4	FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)					
PoE	PoE Standard	-	-	802.3af/802.3at		-	-
	PoE Port	-	-	24	24	-	-
	PoE Budget	-	-	400 watts	400 watts	-	-
	PSE Type	-	-	End-span	End-span	-	-
	Power Pin Assignment	-	-	1/2(+), 3/6(-)	1/2(+), 3/6(-)	-	-
Layer 3 Features	IP Interfaces	128 VLAN	128 VLAN	128 VLAN	128 VLAN	8 VLAN	8 VLAN
	Routing Tables	128	128	128	128	32	32
	Routing Protocols	OSPFv2, IPV6/IPv4 Static Routing		OSPFv2, IPV6/IPv4 Static Routing		IPV6/IPv4 Static Routing	
	Accelerated Hardware	●	●	●	●	-	-
Protocol	VLAN	Port-based VLAN/IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/MAC-based VLAN/Protocol-based VLAN/Voice VLAN/MVR					
	IGMP Snooping	v1/v2/v3/query		v1/v2/v3/query		v1/v2/v3/query	
	Spanning Tree	802.1w/802.1s		802.1w/802.1s		802.1w/802.1s	
	Data Redundancy	ERPS Ring < 10ms		ERPS Ring < 10ms		ERPS Ring < 10ms	
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN					
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security					
	Traffic Control	In/out rate limit, storm control					
Management	Interface	Console, Web, telnet, SSHv2 and TLSv1.2				Console, Web, telnet, SSH and SSL	
	SNMP	v1, v2c, v3 and trap					
	Alarm	Power and port alarm					
	System Log	System Log and remote Syslog					

Metro Fiber Switches


	13" Rackmount	19" Rackmount	
Model	MGSD-10080F	MGSW-24160F	MGSW-28240F

Product Image




Hardware	10/100/1000BASE-T	2	8	4 (Combo)
	10/100BASE-TX	-	-	-
	1000/2500BASE-X	2 x 2500 6 x 1000	16 x 1000	10 x 2500 14 x 1000
	100BASE-FX	Compatible	Compatible	Compatible
	10G SFP+ Slot	-	-	4 (1000X Compatible)
	Switch Fabric	20Gbps	48Gbps	128Gbps
	DI & DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 2 DO
Power	Inputs	Dual 36~72V DC 100~240V AC	Dual 36~60V DC 100~240V AC	Dual 36~60V DC 100~240V AC
	Connector	6-pin terminal block, AC socket		
	Consumption	11.2 watts	45 watts	54 watts
Mechanical	Dimensions (W x D x H)	330 x 155 x 43.5 mm	440 x 200 x 44.5 mm	440 x 200 x 44.5 mm
	Enclosure	Metal chassis	Metal chassis	Metal chassis
	Mounting	Rackmount	Rackmount	Rackmount
Environment	Operating Temperature	-10~60 degrees C	-10~60 degrees C	-10~60 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		
Regulatory	Emissions	FCC Class A, CE Class A		
	Stability	-	-	-
PoE	PoE Standard	-	-	-
	PoE Port	-	-	-
	PoE Budget	-	-	-
	PSE Type	-	-	-
	Power Pin Assignment	-	-	-
Layer 3 Features	IP Interfaces	8 VLAN	8 VLAN	128 VLAN
	Routing Tables	32	32	128
	Routing Protocols	IPv6/IPv4 Static Routing		OSPFv2, IPv6/IPv4 Static Routing
	Accelerated Hardware	-	-	•
Protocol	VLAN	Port-based VLAN/IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/MAC-based VLAN/Protocol-based VLAN/Voice VLAN/MVR		
	IGMP Snooping	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring < 10ms	RSTP/MSTP	ERPS Ring < 10ms
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN		
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security		
	Traffic Control	In/out rate limit, storm control		
Management	Interface	Console, Web, telnet, SSH and SSL		
	SNMP	v1, v2c, v3 and trap		
	Alarm	Power and port alarm		
	System Log	System Log and remote Syslog		

Fully Front Panel Access Design




AC Power, DC Power, Digital I/O, and Network Access are all managed on the front panel.

Digital Input



Designed for intrusion and environment detection to protect the assets.

Digital Output



Designed for AC, DC, link alteration

DIN-rail L3/L2+ Managed Ethernet Switches

		L3				L2+ Ring	
Model		IGS-5225-8T2S2X	IGS-6325-8T8S4X	IGS-6325-8T8S	IGS-6325-8T4X	IGS-20040MT	IGS-12040MT
Product Image							
		Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP
Hardware	10/100/1000BASE-T	8	8	8	8	16	8
	10/100BASE-TX	-	-	-	-	-	-
	1000/2500BASE-X	2	8	8	Compatible	4 x 1000	4 x 1000
	100BASE-FX	Compatible	Compatible	Compatible	-	Compatible	Compatible
	10G SFP+ Slot	2	4	-	4	-	-
	Switch Fabric	66Gbps	112Gbps	56Gbps	96Gbps	40Gbps	24Gbps
	DI & DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 2 DO
Power	Inputs	Dual 12-48V DC or 24V AC		Dual 12-48V DC or 24V AC		Dual 12-48V DC or 24V AC	Dual 12-72V DC or 24V AC
	Connector	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block
	Consumption	20 watts	30 watts(TBD)	25 watts(TBD)	30 watts	17 watts	12 watts
Mechanical	Dimensions (W x D x H)	76 x 107 x 152 mm		76 x 107 x 152 mm		76 x 107 x 152 mm	
	Enclosure	IP30 aluminum		IP30 aluminum		IP30 aluminum	
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Environment	Operating Temperature	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)	5%~70% RH(Non-condensing)			5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)					
PoE	PoE Standard	-	-	-	-	-	-
	PoE Port	-	-	-	-	-	-
	PoE Budget	-	-	-	-	-	-
	PSE Type	-	-	-	-	-	-
	Power Pin Assignment	-	-	-	-	-	-
Layer 3 Features	IP Interfaces	128 VLAN	128 VLAN	128 VLAN	128 VLAN	8 VLAN	8 VLAN
	Routing Tables	128	128	128	128	32	32
	Routing Protocols	OSPFv2, IPV6/IPv4 Static Routing		OSPFv2, IPV6/IPv4 Static Routing		IPV6/IPv4 Static Routing	
	Accelerated Hardware	●	●	●	●	-	-
Protocol	VLAN	Port-based VLAN/IEEE 802.0Q VLAN/Q-in-Q/Private VLAN/Mac-based VLAN/Protocol-based VLAN/Voice VLAN/MVR/GVRP					
	IGMP Snooping	v1/v2/v3/query		v1/v2/v3/query		v1/v2/v3/query	
	Spanning Tree	802.1w/802.1s		802.1w/802.1s		802.1w/802.1s	
	Data Redundancy	ERPS Ring < 10ms		ERPS Ring < 10ms		ERPS Ring < 10ms	
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN					
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security					
	Traffic Control	In/out rate limit, storm control		In/out rate limit, storm control		In/out rate limit, storm control	
Management	Interface	Console, Web, telnet, SSHv2 and TLSv1.2		Console, Web, telnet, SSHv2 and TLSv1.2		Console, Web, telnet, SSHv2 and TLSv1.2	
	SNMP	v1, v2c, v3 and trap		v1, v2c, v3 and trap		v1, v2c, v3 and trap	
	Alarm	Power and port alarm		Power and port alarm		Power and port alarm	
	System Log	System Log and remote Syslog		System Log and remote Syslog		System Log and remote Syslog	

	L2+ Ring			L2/L4			
Model	IGS-10020MT	IGS-10080MFT	IGS-5225-4T2S	IGS-4215-4T2S	IGS-4215-8T2S	IGS-4215-16T2S	IGS-801M



Hardware	10/100/1000BASE-T	8	2	4	4	8	16	8
	10/100BASE-TX	-	-	-	-	-	-	-
	1000/2500BASE-X	2	2 x 2500 6 x 1000	2 x 1000	2 x 1000	2 x 1000	2 x 1000	-
	100BASE-FX	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	-
	10G SFP+ Slot	-	-	-	-	-	-	-
	Switch Fabric	26Gbps	26Gbps	12Gbps	12Gbps	20Gbps	36Gbps	16Gbps
	DI & DO	-	-	-	-	-	-	-
Power	Inputs	Dual 12-48V DC or 24V AC			Dual 9-48V DC or 24V AC		Dual 12-48V DC or 24V AC	
	Connector	6-pin terminal block			6-pin terminal block		6-pin terminal block	
	Consumption	10 watts	13.92 watts	6.5 watts	7 watts	7 watts	15 watts	10 watts
Mechanical	Dimensions (W x D x H)	56 x 87.8 x 135 mm	76 x 107 x 152 mm	32 x 87 x 135 mm	32 x 87 x 135 mm	50 x 87.8 x 135 mm	72 x 107 x 152 mm	32 x 87 x 135 mm
	Enclosure	IP30 aluminum		IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable			DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Environment	Operating Temperature	-40-75 degrees C			-40-75 degrees C		-40-75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)			5%-70% RH(Non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A			FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)			IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)			
PoE	PoE Standard	-	-	-	-	-	-	-
	PoE Port	-	-	-	-	-	-	-
	PoE Budget	-	-	-	-	-	-	-
	PSE Type	-	-	-	-	-	-	-
	Power Pin Assignment	-	-	-	-	-	-	-
Layer 3 Features	IP Interfaces	8 VLAN	8 VLAN	8 VLAN	-	-	-	-
	Routing Tables	32	32	32	-	-	-	-
	Routing Protocols	IPv6/IPv4 Static Routing			-	-	-	-
	Accelerated Hardware	-	-	-	-	-	-	-
Protocol	VLAN	Port-based VLAN/IEEE 802.0Q VLAN/Q-in-Q/Private VLAN/Mac-based VLAN/Protocol-based VLAN/Voice VLAN/MVR/GVRP			IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP			
	IGMP Snooping	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query	v2/v3/query	v2/v3/query	v2/v3/query	
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	
	Data Redundancy	ERPS Ring < 10ms	ERPS Ring < 10ms	ERPS Ring < 10ms	ERPS Ring	ERPS Ring	ERPS Ring	
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN			Port-based/802.1P/IP DSCP Policy-based/Voice VLAN			
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security			802.1x, Static MAC, MAC filter, Port Security and IP Security			
	Traffic Control	In/out rate limit, storm control			In/out rate limit, storm control			
Management	Interface	Web, telnet, SSHv2 and TLSv1.2	Console, Web, telnet, SSHv2 and TLSv1.2		Web, Tlenet, SSHv2 and TLSv1.2		Web, telnet, SSH and TLSv1.2	
	SNMP	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap		v1, v2c, v3 and trap	
	Alarm	Power alarm	Power alarm	Power alarm	Power and port alarm		Power alarm	
	System Log	System Log and remote Syslog			System Log and remote Syslog		System Log and remote Syslog	

DIN-rail L3/L2+ Power over Ethernet Managed Ethernet Switches

		802.3bt PoE++				802.3at PoE+	
Model	IGS-5225-4UP1T2S	IGS-6325-8UP2S2X IGS-6325-8UP2S	IGS-6329-8UP2S2X	IGS-6329-8UP2S4X	IGS-6325-16P4S	IGS-5225-8P2S2X	
Product Image							
							
Hardware	10/100/1000BASE-T	5	8	8	8	16	8
	10/100BASE-TX	-	-	-	-	-	-
	1000/2500BASE-X	2 x 1000	2	2	2	4	2 x 1000
	100BASE-FX	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible
	10G SFP Slot	-	2/-	2	4	-	2
	Switch Fabric	14Gbps	60/26Gbps	60Gbps	100Gbps	52Gbps	60Gbps
	DI & DO	2 DI & DO	2 DI & DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & DO	2 DI & DO
Power	Inputs	Dual 48-56V DC	Dual 48-56V DC	Dual 48-54V DC	Dual 48-56V DC	Dual 48-56V DC	Dual 48-56V DC
	Connector	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block
	Consumption	280 watts	340/335 watts	401 watts	405 watts	440 watts	300 watts
Mechanical	Dimensions (W x D x H)	76 x 107 x 152 mm	76 x 107 x 152 mm	76 x 135 x 152 mm	76 x 135 x 152 mm	82 x 107 x 152 mm	76 x 107 x 152 mm
	Enclosure	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP30 aluminum
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Environment	Operating Temperature	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)		5%~70% RH (Non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)		FCC Class A, EN 61000-6-2, EN 61000-6-4, EN50121-4		IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)	
PoE	PoE Standard	802.3bt PoE++	802.3bt PoE++	802.3bt PoE++	802.3bt PoE++	802.3af/802.3at	802.3af/802.3at
	PoE Port	4	8	8	8	16	8
	PoE Budget	240 watts	320 watts	360 watts	360 watts	320 watts max.	270 watts max.
	PSE Type	Mid-span + End-span		Mid-span + End-span	Mid-span + End-span	End-span	End-span
	Power Pin Assignment	Pair1: 1/2(-), 3/6(+) Pair2: 4/5(+), 7/8(-)		Pair 1: 1/2(-), 3/6(+) Pair 2: 4/5(+), 7/8(-)	Pair 1: 1/2(-), 3/6(+) Pair 2: 4/5(+), 7/8(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
Layer 3 Features	IP Interfaces	8 VLAN	128 VLAN	128 VLAN	128 VLAN	128 VLAN	128 VLAN
	Routing Tables	32	128	128	128	128	128
	Routing Protocols	IPv6/IPv4 Static Routing	OSPFv2/v3, RIPv1/v2, IPv6/IPv4 Static Routing			OSPFv2, IPv6/IPv4 Static Routing	
	Accelerated Hardware	-	•	•	•	•	•
Protocol	VLAN	Port-based VLAN/IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Mac-based VLAN/Protocol-based VLAN/Voice VLAN/MVR/GVRP					
	IGMP Snooping	v1/v2/v3/query		v1/v2/v3/query		v1/v2/v3/query	
	Spanning Tree	802.1w/802.1s		802.1w/802.1s		802.1w/802.1s	
	Data Redundancy	ERPS Ring < 10ms		ERPS Ring < 10ms		ERPS Ring < 10ms	
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN					
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security					
	Traffic Control	In/out rate limit, storm control		In/out rate limit, storm control		In/out rate limit, storm control	
Management	Interface	Console, Web, telnet, SSHv2 and TLSv1.2					
	SNMP	v1, v2c, v3 and trap					
	Alarm	Power and port alarm					
	System Log	System Log and remote Syslog					

DIN-rail L3/L2+ Power over Ethernet Managed Ethernet Switches

802.3at PoE+							
Model	IGS-5225-8P4S	IGS-5225-8P2T2S	IGS-5225-8P2T4S	IGS-10020HPT IGS-10020PT	IGS-20160HPT	IGS-5225-4P2S	
Product Image							
	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	
Hardware	10/100/1000BASE-T	8	8	8	8	18	4
	10/100BASE-TX	-	2	-	-	-	-
	1000/2500BASE-X	4 x 1000	2 x 1000	2 x 1000 2 x 1000/2500	2	2	2 x 1000
	100BASE-FX	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible
	10G SFP Slot	-	-	-	-	-	-
	Switch Fabric	24Gbps	20Gbps	34Gbps	26Gbps	46Gbps	12Gbps
	DI & DO	2 DI & DO	2 DI & DO	2 DI & 2 DO	2 DI & DO	2 DI & DO	-
Power	Inputs	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC	Dual 12~48V DC/Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC
	Connector	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block	6-pin terminal block
	Consumption	300 watts	300 watts	262 watts	306/161.9 watts	440 watts	140 watts
Mechanical	Dimensions (W x D x H)	76 x 107 x 152 mm	76 x 107 x 152 mm	76 x 107 x 152 mm	76 x 107 x 152 mm	82 x 107 x 152 mm	56 x 87 x 135 mm
	Enclosure	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP30 aluminum	IP40 metal
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Environment	Operating Temperature	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)		5%~70% RH (Non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)		IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)		IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)	
PoE	PoE Standard	802.3af/802.3at	802.3af/802.3at	802.3at PoE+	802.3af/802.3at	802.3af/802.3at	802.3af/802.3at
	PoE Port	8	8	8	8	16	4
	PoE Budget	240 watts max.	240 watts max.	240 watts	270/240 watts max.	320 watts max.	120 watts max.
	PSE Type	End-span	End-span	End-span	End-span	End-span	End-span
	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	Pair 1: 1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
Layer 3 Features	IP Interfaces	8 VLAN	8 VLAN	8 VLAN	8 VLAN	128 VLAN	8 VLAN
	Routing Tables	32	32	32	32	128	32
	Routing Protocols	IPv6/IPv4 Static Routing		IPv6/IPv4 Static Routing		IPv6/IPv4 Static Routing	
	Accelerated Hardware	-	-	-	-	●	-
Protocol	VLAN	802.1Q VLAN/Q-in-Q/Private VLAN/MAC-based VLAN/Protocol-based VLAN/Voice VLAN/MVR/GVRP					
	IGMP Snooping	v1/v2/v3/query		v1/v2/v3/query		v1/v2/v3/query	
	Spanning Tree	802.1w/802.1s		802.1w/802.1s		802.1w/802.1s	
	Data Redundancy	ERPS Ring < 10ms		ERPS Ring < 10ms		ERPS Ring < 10ms	
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN					
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security					
	Traffic Control	In/out rate limit, storm control		In/out rate limit, storm control		In/out rate limit, storm control	
Management	Interface	Console, Web, telnet, SSHv2 and TLSv1.2					
	SNMP	v1, v2c, v3 and trap					
	Alarm	Power and port alarm					
	System Log	System Log and remote Syslog					


DIN-rail L2/L4 Power over Ethernet Managed Switches

		802.3at PoE+		
Model		IGS-4215-4P4T	IGS-4215-4P4T2S	IGS-4215-8P2T2S
Product Image				
Hardware	10/100/1000BASE-T	8	8	10
	10/100BASE-TX	-	-	-
	1000 mini-GBIC	-	2	2
	100BASE-FX	-	Compatible	Compatible
	Switch Fabric	16Gbps	20Gbps	24Gbps
Power	DI & DO	-	-	-
	Inputs	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC
	Connector	6-pin terminal block	6-pin terminal block	6-pin terminal block
Mechanical	Consumption	160 watts	170 watts	280 watts
	Dimensions (W x D x H)	76 x 107 x 152 mm	76 x 107 x 152 mm	76 x 107 x 152 mm
	Enclosure	IP30 aluminum	IP30 aluminum	IP30 aluminum
Environment	Mounting	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable
	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
Regulatory	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)
	Emissions	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A
PoE	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
	PoE Standard	802.3af/802.3at	802.3af/802.3at	802.3af/802.3at
	PoE Port	4	4	8
	PoE Budget	144 watts	144 watts	240 watts
	PSE Type	End-span	End-span	End-span
Layer 3 Features	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
	IP Interfaces	-	-	-
	Routing Tables	-	-	-
	Routing Protocols	-	-	-
Protocol	Accelerated Hardware	-	-	-
	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP		
	IGMP Snooping	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring	ERPS Ring	ERPS Ring
Management	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN		
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security		
	Traffic Control	In/out rate limit, storm control		
Management	Interface	Console, Web, telnet, SSHv2, TSL v1.2 and SSL		
	SNMP	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap
	Alarm	Power alarm	Power alarm	Power and port alarm
	System Log	System Log and remote Syslog		

Renewable Energy PoE Switch

Model		BSP-360
Product Image		
LAN	10/100/1000	5
PoE	802.3at	4
PoE Budget		per port 30 watts (max.)
PSE Type		end-span
PoE Power Pin		1/2(+), 3/6 (-)
PoE Power Voltage		52V DC
Management		Web/SNMP
System Voltage/Battery Requirement		24V DC
Power IN		Solar or turbines 24~45V DC
Max. Charge Current		8.8A
Features		<ul style="list-style-type: none"> * 24V DC, 1A output load * Low voltage protection and alert * PoE schedule and management * USB Backup

Renewable Energy Off-Grid PoE+ Network System Application



Note: Check the total power consumption of your device and the sunshine duration of your area from weather bureau for a proper PV. Improper PV could shorten the battery life or provide insufficient power to Renewable Energy PoE Switch.

Industrial Power over Ethernet Unmanaged Switches

802.3at PoE+							
Model	ISW-504PT	ISW-514PTF	IGS-504PT	IGS-504HPT	IGS-614HPT	IGS-624HPT	
Product Image							Redundant Fiber
Hardware	10/100/1000BASE-T	-	-	5	5	5	4
	10/100BASE-TX	5	4	-	-	-	-
	1000BASE-SX/LX	-	-	-	-	1	2, compatible with 2500X
	100BASE-FX	-	1	-	-	Compatible	Compatible
	Fiber Connector Type	-	SFP	-	-	SFP	SFP
	Switch Fabric	1Gbps	1Gbps	10Gbps	10Gbps	12Gbps	12Gbps
	MAC Table	1K	1K	2K	2K	2K	4K
Mechanical	Dimensions (W x D x H)	50 x 87.8 x 135 mm	50 x 87.8 x 135 mm	30 x 70 x 104 mm	50 x 87 x 135 mm	50 x 87 x 135 mm	50 x 87 x 135 mm
	Enclosure	IP40 metal	IP40 metal	IP30 metal	IP40 metal	IP40 metal	IP40 metal
	Power Requirement	Dual 12~48V DC	Dual 12~48V DC	Dual 48~54V DC	Dual 12~56V DC	Dual 12~56V DC	Dual 12~56V DC
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Regulatory	EMI/Safety		FCC Class A, CE		FCC Class A, CE Class A		FCC Class A, CE
Environment	Operating Temperature		-40~75 degrees C		-40~75 degrees C		-40~75 degrees C
PoE	PoE Standard	802.3at	802.3at	802.3at	802.3at	802.3at	802.3at
	PoE Port	4	4	4	4	4	4
	PoE Budget	60 watt max. @ 12V DC 120 watts max. @ 24~48V DC		120 watts		60 watt max. @ 12V DC 120 watts max. @ 24~48V DC	
	PSE Type	End-span		End-span		End-span	
	Power Pin Assignment	1/2(+), 3/6(-)		1/2(+), 3/6(-)		1/2(+), 3/6(-)	

802.3at PoE+					802.3bt PoE++	
Model	IGS-1020PTF	IGS-1020PTF-12V	IFGS-1022HPT	IPOE-E174	IGS-824UPT	
Product Image						PoE Extension
Hardware	10/100/1000BASE-T	8	8	2	5	6
	10/100BASE-TX	-	-	8	-	-
	1000BASE-SX/LX	2	2	2	-	2
	100BASE-FX	Compatible	Compatible	-	-	Compatible
	Fiber Connector Type	SFP	SFP	SFP	-	SFP
	Switch Fabric	20Gbps	20Gbps	5.6Gbps	10Gbps	16Gbps
	MAC Table	8K	8K	16K	8K	8K
Mechanical	Dimensions (W x D x H)	76 x 107 x 152 mm	76 x 107 x 152 mm	72 x 105 x 152 mm	32 x 87.8 x 135 mm	50 x 87 x 135 mm
	Enclosure	IP30 metal	IP30 aluminum	IP30 aluminum	IP30 metal	IP30 metal
	Power Requirement	Dual 48~56V DC	Dual 12~56V DC	48~56V DC	End-span + Mid-span 802.3bt PoE++ PD	48~56V DC
	Mounting	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable	
Regulatory	EMI/Safety		FCC Class A, CE Class A		FCC Class A, CE	
Environment	Operating Temperature		-40~75 degrees C		-40~75 degrees C	
PoE	PoE Standard	802.3at	802.3at	802.3at	802.3af/802.3at	802.3bt
	PoE Port	8	8	8	4	4
	PoE Budget	240 watts	60 watts max. @12V DC 120 watts max. @24V DC 240 watts max. @48~56V DC	240 watts max.	50 watts max.	240 watts max.
	PSE Type	End-span	End-span	End-span	End-span	Mid-span + End-span
	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(-), 3/6(+) 4/5(+), 7/8(-)

EN50155 Railway/Ethernet Switches & Extenders

		802.3at PoE+				L2+ Ring	
Model		IGS-5227X-4P2T	IGS-604HPT-M12	IGS-604HPT-RJ	IGS-5226-4P2T	IGS-5227-6MT-X	IGS-5227-6T
Product Image							
		Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP	Modbus TCP
Hardware	10/100/1000BASE-T	6 x M12, 8-pin X-coded connector	6 x M12, 8-pin A-coded connector	6 x Waterproof RJ45	6 x Waterproof RJ45	6 x M12, 8-pin X-coded connector	6 x Waterproof RJ45
	1000 mini-GBIC	-	-	-	-	-	-
	100BASE-FX	-	-	-	-	-	-
	Switch Fabric	12Gbps	12Gbps	12Gbps	12Gbps	12Gbps	12Gbps
	DI & DO	-	-	-	-	-	-
Power	Inputs	Dual 12~48V DC	Dual 48~56V DC	Dual 48~56V DC	Dual 48~56V DC	Dual 9~48V DC	Dual 9~48V DC
	Connector	5-pin M23 male connector	5-pin A-Coded M12 male connector			5-pin A-Coded M12 male connector	
	Consumption	160 watts	160 watts	160 watts	160 watts	10 watts	10 watts
Mechanical	Dimensions (W x D x H)	163 x 103 x 53 mm	163 x 103 x 53 mm	163 x 103 x 53 mm	163 x 103 x 53 mm	163 x 103 x 53 mm	163 x 103 x 53 mm
	Enclosure	IP67 aluminum	IP67 aluminum	IP67 aluminum	IP50 metal	IP67 aluminum	IP67 aluminum
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)				IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)	
PoE	PoE Standard	802.3af/802.3at	802.3af/802.3at	802.3af/802.3at	802.3af/802.3at	-	-
	PoE Port	4	4	4	4	-	-
	PoE Budget	60 watts max.@12V DC 90 watts max.@24V DC 144 watts max. @48~56V DC	144 watts	144 watts	144 watts	-	-
	PSE Type	End-span	End-span	End-span	End-span	-	-
	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	-	-
Layer 3 Features	IP Interfaces	8 VLAN	8 VLAN	8 VLAN	8 VLAN	8 VLAN	8 VLAN
	Routing Tables	32	32	32	32	32	32
	Routing Protocols	IPv6/IPv4 Static Routing		IPv6/IPv4 Static Routing		IPv6/IPv4 Static Routing	
	Accelerated Hardware	-	-	-	-	-	-
Protocol	VLAN	Port-based VLAN/IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/MAC-based VLAN/Protocol-based VLAN/Voice VLAN/MVR				802.1Q VLAN/Q-in-Q/Private VLAN/MAC-based VLAN, Protocol-based VLAN/Voice VLAN/MVR	
	IGMP Snooping	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query	v1/v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring < 20ms	ERPS Ring < 20ms	ERPS Ring < 20ms	ERPS Ring < 20ms	ERPS Ring < 20ms	ERPS Ring < 20ms
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN					
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security					
Traffic Control	In/out rate limit, storm control						
Management	Interface	Web, telnet, SSH and SSL		Web, telnet, SSH and SSL		Web, telnet, SSH and SSL	
	SNMP	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap	v1, v2c, v3 and trap	
	Alarm	Power and port alarm		Power alarm		Power and port alarm	
	System Log	System Log and remote Syslog		System Log and remote Syslog		System Log and remote Syslog	

EN50155 Railway/Ethernet Switches & Extenders

M12 Switches				RJ45 Extenders	
Model	ISW-800T-M12	ISW-808PT-M12	ISW-800PT-M12A	IPOE-E302	
Product Image					
				95W	
Hardware	Interface	8 x M12, 4-pin D-coded connector	8 x M12, 4-pin D-coded connector	8 x M12, 4-pin D-coded connector	3 x IP67 waterproof RJ45
	Data Rate	10/100Mbps	10/100Mbps	10/100Mbps	10/100/1000Mbps
	Power over Ethernet	-	8-port 802.3at PoE+	8-port 802.3at PoE+	1-port 802.3bt PoE PD 2-port 802.3bt/at PoE PSE
	Switch Fabric	1.6Gbps	1.6Gbps	1.6Gbps	6Gbps
Mechanical	Dimensions (W x D x H)	103 x 53 x 163 mm	103 x 53 x 163 mm	103 x 53 x 163 mm	150 x 72 x 44 mm
	Weight	976g	1,150g	1,150g	320g
	Enclosure	IP67 aluminum	IP67 aluminum	IP50 metal	IP67 aluminum
	Mounting	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable	Wall-mountable
Power	Inputs	Dual 12-48V DC	Dual 12-56V DC	Dual 12-56V DC	50-57V DC PoE
	Connector	5-pin A-coded M12 male connector	5-pin A-coded M23 male connector		RJ45
	Consumption	4 watts	250 watts	250 watts	60-95 watts
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)
Regulatory	Emissions/Safety	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)			

Flat-type Unmanaged Ethernet Switches

Switch			PoE+ Switch			
Model	WGS-810	WGS-803	WGS-804HP	WGS-818HP	WGS-814HP	
Product Image						
Hardware	10/100/1000BASE-T	8	8	8	8	
	10/100BASE-TX	-	-	-	-	
	1000 mini-GBIC	-	-	-	-	
	100BASE-FX	-	-	-	-	
	Fiber Connector Type	-	-	-	-	
	Switch Fabric	16Gbps	16Gbps	16Gbps	16Gbps	16Gbps
Power	Inputs	12V DC	12-48V DC or 24V AC	Dual 48-56V DC	Dual 48-56V DC	Dual 48-56V DC
	Connector	DC Socket	3-pin terminal block, DC socket		DC Socket	DC Socket
Mechanical	Dimensions (W x D x H)	148 x 25 x 134 mm	148 x 25 x 134 mm	148 x 25 x 134 mm	148 x 25 x 134 mm	148 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-20~60 degrees C	-10~60 degrees C	-10~60 degrees C	-20~60 degrees C	-20~60 degrees C
Regulatory	Emissions	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A
PoE	PoE Standard	-	-	802.3af/802.3at	802.3af/802.3at	802.3af/802.3at
	PoE Port	-	-	4	8	4
	PoE Budget	-	-	120 watts	120 watts	60 watts
	PSE Type	-	-	End-span	End-span	End-span
	Power Pin Assignment	-	-	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)

Flat-type Managed Ethernet Switches

	L2/L2+ Switches				L2/L2+ PoE+ Switches			
Model	WGS-4215-8T	WGS-4215-8T2S	WGS-5225-8T2SV	WGS-5225-8UP2SV	WGS-5225-8P2SV	WGS-5225-8P2S	WGS-4215-16P2S	

Product Image



Hardware	LCD	-	-	2.4" Color TFT touch screen			-	-
	10/100/1000BASE-T	8	8	8	8	8	8	16
	10/100BASE-TX	-	-	-	-	-	-	-
	1000/2500BASE-X	-	2 x 1000	2	2	2	2	2 x 1000
	100BASE-FX	-	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible
	10G SFP+ Slot	-	-	-	-	-	-	-
	Switch Fabric	16Gbps	20Gbps	26Gbps	26Gbps	26Gbps	26Gbps	36Gbps
DI/DO	-	-	-	-	-	-	-	
Power	Inputs	12-48V DC or 24V AC			Dual 48-54V DC	Dual 48-56V DC	Dual 48-56V DC	Dual 48-56V DC
	Connector	3-pin terminal block, DC socket			3-pin terminal block, DC socket	3-pin terminal block, DC socket		
	Consumption	7 watts	7.9 watts	12 watts	750 watts	215 watts	210 watts	240 watts
Mechanical	Dimensions (W x D x H)	148 x 25 x 134 mm	178 x 25 x 134 mm		178 x 25 x 134 mm	178 x 25 x 134 mm	178 x 25 x 134 mm	245 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 Aluminum	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount			DIN-rail, wall-mountable and magnetic wall mount			
Environment	Operating Temperature	-40-75 degrees C		-20-70 degrees C	-20-70 degrees C		-40-75 degrees C	-10-60 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)			5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A			FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)			IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)			
PoE	PoE Standard	-	-	-	802.3bt PoE++	802.3at PoE+	802.3at PoE+	802.3at
	PoE Port	-	-	-	8	8	8	8
	PoE Budget	-	-	-	720 watts	200 watts	200 watts	240 watts
	PSE Type	-	-	-	End-sapn+Mid-sapn	End-sapn	End-sapn	End-sapn
	Power Pin Assignment	-	-	-	1/2(-), 3/6(+) 4/5(+),7/8(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
Layer 3 Features	IP Interfaces	-	-	8 VLAN	8 VLAN	8 VLAN	8 VLAN	-
	Routing Tables	-	-	32	32	32	32	-
	Routing Protocols	-	-	IPv6/IPv4 Static Routing	IPv6/IPv4 Static Routing	IPv6/IPv4 Static Routing	IPv6/IPv4 Static Routing	-
	Accelerated Hardware	-	-	-	-	-	-	-
Protocol	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP						
	IGMP Snooping	v2/v3/query	v2/v3/query	V1/v2/v3/query	V1/v2/v3/query	V1/v2/v3/query	V1/v2/v3/query	v2/v3/query
	Spanning Tree	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s	802.1w/802.1s
	Data Redundancy	ERPS Ring	ERPS Ring	ERPS Ring < 10ms	ERPS Ring < 10ms	ERPS Ring < 10ms	ERPS Ring < 10ms	ERPS Ring
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN						
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security						
	Traffic Control	In/out rate limit, storm control						
Management	Interface	Web, telnet, SSHv2 and TLSv1.2		Web, telnet, SSH and SSL		Web, telnet, SSH and SSL		Web, telnet, SSHv2 and TLSv1.2
	SNMP	v1, v2c, v3 and trap		v1, v2c, v3 and trap		v1, v2c, v3 and trap		
	Alarm	-	-	-	-	-	-	-
	System Log	System Log and remote Syslog		System Log and remote Syslog		System Log and remote Syslog		

Flat-type Managed Ethernet Switches

Flat-type Gigabit Routers

L2/L4 PoE+ Switches			
Model	WGS-4215-8HP2S	WGS-4215-8P2S	WGS-804HPT

Touch LCD		Managed PoE+	Managed
Model	WGR-500-4PV	WGR-500-4P	WGR-500

Product Image



Product Image



Hardware	LCD	-	-	-
	10/100/1000BASE-T	8	8	8
	10/100BASE-TX	-	-	-
	1000 mini-GBIC	2	2	-
	100BASE-FX	Compatible	Compatible	-
	10G SFP+ Slot	-	-	-
	Switch Fabric	20Gbps	20Gbps	16Gbps
	DI/DO	-	-	-
Power	Inputs	Dual 48~56V DC		
	Connector	3-pin terminal block, DC socket		
	Consumption	350 watts	210 watts	152 watts
Mechanical	Dimensions (W x D x H)	178 x 25 x 134 mm	178 x 25 x 134 mm	148 x 25 x 134 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-40~75 degrees C		
	Operating Humidity	5% to 95%RH (non-condensing)		
Regulatory	Emissions	FCC Class A, CE Class A		
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
PoE	PoE Standard	802.3bt/802.3at	802.3at	802.3at
	PoE Port	4 x 802.3bt 4 x 802.3at	8	4
	PoE Budget	320 watts	200 watts	144 watts
	PSE Type	End-sapn+Mid-sapn	End-sapn	End-sapn
	Power Pin Assignment	1/2(-), 3/6(+) 4/5(+), 7/8(-)	1/2(+), 3/6(-)	1/2(+), 3/6(-)
	Layer 3 Features	IP Interfaces	-	-
	Routing Tables	-	-	-
	Routing Protocols	-	-	-
	Accelerated Hardware	-	-	-
Protocol	VLAN	IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP		
	IGMP Snooping	v2/v3/query		
	Spanning Tree	802.1w/802.1s		
	Data Redundancy	ERPS Ring		
	QoS	Port-based/802.1P/IP DSCP Policy-based/Voice VLAN		
	Security	802.1x, Static MAC, MAC filter, Port Security and IP Security		
	Traffic Control	In/out rate limit, storm control		
Management	Interface	Web, telnet, SSHv2 and TLSv1.2		
	SNMP	v1, v2c, v3 and trap		
	Alarm	-	-	-
	System Log	System Log and remote Syslog		

Hardware	LCD	2.4" Color TFT Touch Screen	-	-
	10/100/1000BASE-T	5 (4 LAN, 1 WAN)		
Power	Inputs	Dual 48~56V DC		Dual 9~48V DC
	Connector	3-pin terminal block, DC socket		2-pin terminal block, DC socket
Mechanical	Dimensions (W x D x H)	180 x 25 x 140 mm		148 x 24 x 134 mm
	Enclosure	IP30 metal		
	Mounting	DIN-rail, wall-mountable and magnetic wall mount		
Environment	Operating Temperature	-10~60 degrees C		
	Operating Humidity	5% to 95%RH (non-condensing)		
Regulatory	Emissions	FCC Class A, CE Class A		
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)		
PoE	PoE Standard	802.3at PoE+		-
	PoE Port	4	4	-
	PoE Budget	120 watts	120 watts	-
	PSE Type	End-span	End-span	-
	Power Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-)	-
	Protocol	VLAN	IEEE 802.1Q VLAN	
Management	Interface	Web	Web	Web
	SNMP	v1, v2c	v1, v2c	v1, v2c
	System Log	System log and remote Syslog		

Unique Flat-type Design with Touch LCD



Front Access



Flat Design



PoE Usage



DIN-rail Installation



Fiber Connection



Magnetic Installation

Industrial Long Reach PoE Switches, Injectors & Extenders

	Long Reach PoE Injectors		Switch	Long Reach PoE Extenders	
Model	LRP-101CH	LRP-101UH	LRP-422CST	LRP-101CE	LRP-101UE

Product Image



Ethernet Interfaces	10/100BASE-TX	1 x RJ45 w/ PoE PD		-	1 x RJ45 w/ PoE PSE	
	10/100/1000BASE-T	-	-	2	-	-
	1000BASE-SX/LX	-	-	2 (100BASE-FX Compatible)	-	-
	PoE Power	-	-	-	56V DC, 600mA max.	48~56V DC, 600mA max.
	Cabling	Cat. 5e or above	Cat. 5e or above	Cat. 5e or above	Cat. 5e or above	Cat. 5e or above
	Maximum Distance	100m	100m	100m	100m	100m
Long Reach PoE Interfaces	Connectivity	1 x BNC female (PSE)	1 x RJ45 Copper (PSE)	4 x BNC female (PSE)	1 x BNC female (PD)	1 x RJ45 Copper (PD)
	Cabling	Coaxial cable: 75ohm	Copper: 4-pair or 1-pair UTP	Coaxial cable: 75ohm	Coaxial cable: 75ohm	Copper: 4-pair or 1-pair UTP
	Maximum Distance	1000m	500m	1000m	1000m	500m
	Data Rate	200m: 93Mbps/93Mbps 1000m: 55Mbps/73Mbps	200m: 94Mbps/94Mbps 500m: 30Mbps/30Mbps	200m: 93Mbps/93Mbps 1000m: 52Mbps/50Mbps	200m: 93Mbps/93Mbps 1000m: 55Mbps/73Mbps	200m: 94Mbps/94Mbps 500m: 30Mbps/30Mbps
	Power Output	48~56V DC, 36 watts max.	48~56V DC, 36 watts max.	48~56V DC, 36 watts max.	-	-
	Total Power Budget	36 watts max.	36 watts max.	144 watts max.	-	-
	Encryption	AES128-bit	AES128-bit	AES128-bit	AES128-bit	AES128-bit
PoE Ability	PoE Standard	Power over coaxial	Power over UTP	Power over coaxial	802.3af/802.3at	802.3af/at
	PoE Port	1 x BNC female (PSE)	1 x UTP	4 x BNC female (PSE)	1 x RJ45 (PSE)	1 x RJ45 (PSE)
	PoE Power Output	41~56V DC	41~56V DC	41~56V DC	56V DC, 600mA max.	48~56V DC, 600mA max.
Intelligent Power Control	Over Temperature Protection	-	-	●	-	-
	PD Alive Check	-	-	●	-	-
	PoE Schedule	-	-	●	-	-
	Power Limit	-	-	●	-	-
	Scheduled Power Recycling	-	-	●	-	-
Protocols	VLAN	-	-	802.1Q, Q-in-Q, Voice VLAN, Private VLAN	-	-
	Spanning Tree	-	-	802.1D/802.1w/802.1s	-	-
	IGMP Snooping	-	-	v1, v2, v3	-	-
Management	Interface	-	-	Console, Telnet, HTTP	-	-
	SNMP	-	-	v1, v2c, v3, trap	-	-
	SSH/SSL	-	-	● / ●	-	-
Physical	Dimensions (W x D x H)	94 x 70 x 26mm	94 x 70 x 26mm	72 x 107 x 152 mm	94 x 70 x 26mm	94 x 70 x 26mm
	Power Requirements	DC: 48~56V DC, PoE: 802.3at input	DC: 48~56V DC, PoE: 802.3at input	Dual 48~56V DC	37~56V DC PoC	37~56V DC PoC
	Operating Temperature	-20~70 degrees C	-20~70 degrees C	-40~75 degrees C	-20~70 degrees C	-20~70 degrees C
Regulatory	EMI/Safety	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE
Compatible Models	LRP-101CE LRP-104CET	LRP-101UE LRP-104CET	LRP-101CE	LRP-101CH LRP-422CST LRP-1622CS LRP-822CS	LRP-101UH	

Long Reach PoE Extenders

Model LRP-104CET

Product Image




Ethernet Interfaces	10/100BASE-TX	4 x RJ45 w/ PoE PSE
	10/100/1000BASE-T	-
	1000BASE-SX/LX	-
	PoE Power	56V DC, 600mA max.
	Cabling	Cat. 5e or above
	Maximum Distance	100m
Long Reach PoE Interfaces	Connectivity	1 x BNC female (PD)
	Cabling	Coaxial cable: 75ohm
	Maximum Distance	1000m
	Data Rate	200m: 93Mbps/93Mbps 1000m: 52Mbps/50Mbps
	Power Output	-
	Total Power Budget	-
	Encryption	AES128-bit
	PoE Ability	PoE Standard
PoE Port		4 x RJ45 (PSE)
PoE Power Output		56V DC, 600mA max.
Intelligent Power Control	Over Temperature Protection	-
	PD Alive Check	-
	PoE Schedule	-
	Power Limit	-
	Scheduled Power Recycling	-
Protocols	VLAN	-
	Spanning Tree	-
	IGMP Snooping	-
Management	Interface	-
	SNMP	-
Physical	Dimensions (W x D x H)	107 x 72 x 152 mm
	Power Requirements	37~56V DC PoC/ Dual 48~56V DC
	Operating Temperature	-40~75 degrees C
Regulatory	EMI/Safety	FCC Class A, CE
Compatible Models		LRP-101CH LRP-101UH

Long Reach PoE Solution

Most Cost-effective Extension via Existing Cable

TAIWAN EXCELLENCE 2016



— 100BASE-TX UTP
— 100BASE-TX UTP with PoE
— Coaxial Cable with Data + Power

Unmanaged Fast Ethernet Switches

Fast Ethernet							
Model	ISW-500T	ISW-800T	ISW-501T	ISW-801T	ISW-511*	ISW-511S15 *	
Product Image							
Hardware	10/100BASE-TX	5	8	5	8	4	4
	10/100/1000BASE-T	-	-	-	-	-	-
	100BASE-FX	-	-	-	-	1/Multi-mode/2km	1/Single mode/15km
	Switch Fabric	1Gbps	1.6Gbps	1Gbps	1.6Gbps	1Gbps	1Gbps
	MAC Table	1k	1k	2k	2k	2k	2k
	Memory Buffer	448k bits	448k bits	448k bits	448k bits	448k bits	448k bits
Protocol	Auto-negotiation	●	●	●	●	●	●
	802.3x Flow Control	●	●	●	●	●	●
Power	Inputs	12-48V DC/24VAC, Dual power input			12-48VDC, Dual power input		
	Connector	6-pin Removable Terminal Block		6-pin Removable Terminal Block		6-pin Removable Terminal Block	
	Consumption	2 watts	2.5 watts	3.9 watts	5.1 watts	5.4 watts	5.4 watts
Mechanical	Dimensions (W x D x H)	30 x 70 x 104 mm	41 x 70 x 115mm	32 x 87.8 x 135 mm	32 x 87.8 x 135 mm	32 x 87.8 x 135 mm	
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-Rail, Wall-mountable		DIN-Rail, Wall-mountable		DIN-Rail, Wall-mountable	
Environment	Operating Temperature	-40-75 degrees C		-40-75 degrees C		-10-60 degrees C *	
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions / Safety	FCC Class A, CE Class A, UL		FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)					

Fast Ethernet							
Model	ISW-621*	ISW-621S15 *	ISW-621TF	IFGS-1022TF	ISW-1600T	IFGS-1822TF	
Product Image							
Hardware	10/100BASE-TX	4	4	4	8	16	16
	10/100/1000BASE-T	-	-	-	2	-	2
	100BASE-FX	2/Multi-mode/2km	2/Single mode/15km	2 SFP Slots	2 1000X SFP Slots	-	2 1000X SFP Slots
	Switch Fabric	1.2Gbps	1.2Gbps	1.2Gbps	5.6Gbps	3.2Gbps	3.6Gbps
	MAC Table	2k	2k	2k	16k	2k	2k
	Memory Buffer	448k bits	448k bits	448k bits	4Mbits	4Mbits	4Mbits
Protocol	Auto-negotiation	●	●	●	●	●	●
	802.3x Flow Control	●	●	●	●	●	●
Power	Inputs	12-48VDC, Dual power input	12-48VDC, Dual power input	12-48VDC, Dual power input	12-48VDC, Dual power input	12-48VDC, Dual power input	12-48VDC, Dual power input
	Connector	6-pin Removable Terminal Block		6-pin Removable Terminal Block		6-pin Removable Terminal Block	
	Consumption	7.9 watts	7.9 watts	7.9 watts	7.2 watts	15 watts	15 watts
Mechanical	Dimensions (W x D x H)	32 x 87.8 x 135 mm	32 x 87.8 x 135 mm	32 x 87.8 x 135 mm	50 x 87 x 135 mm	65 x 107 x 152 mm	65 x 107 x 152 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP40 metal	IP40 metal
	Mounting	DIN-Rail, Wall-mountable		DIN-Rail, Wall-mountable		DIN-Rail, Wall-mountable	
Environment	Operating Temperature	-10-60 degrees C *	-10-60 degrees C *	-40-75 degrees C	-40-75 degrees C	-40-75 degrees C	-40-75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions / Safety	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE, UL	FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)					

* Wide Temperature models (-40-75 degrees C): ISW-511T, ISW-511TS15, ISW-621T, ISW-621TS15

Unmanaged Gigabit Ethernet Switches

Gigabit					
Model	IGS-500T	IGS-510TF	IGS-501T	IGS-801T	
Product Image					
Hardware	10/100/1000BASE-T	5	4	5	8
	10/100BASE-TX	-	-	-	-
	1000BASE-SX/LX	-	1 (100BASE-FX Compatible)	-	-
	Switch Fabric	10Gbps	10Gbps	10Gbps	16Gbps
	MAC Table	2k	2k	2k	8k
	Memory Buffer	1Mbits	1Mbits	1Mbits	176k Bytes
Protocol	Auto-negotiation	●	●	●	●
	802.3x Flow Control	●	●	●	●
Power	Inputs	12~48V DC/24V AC, Dual power input	9~48V DC/24V AC, Dual power input	12~48VDC, Dual power input	12~48VDC, Dual power input
	Connector	6-pin removeable terminal block	4-pin removeable terminal block	6-pin removeable terminal block	6-pin removeable terminal block
	Consumption	5.28 watts	4.3 watts	5.28 watts	6.7 watts
Mechanical	Dimensions (W x D x H)	30 x 10 x 104 mm	30 x 10 x 104 mm	32 x 87.8 x 135 mm	32 x 87.8 x 135 mm
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)
Regulatory	Emissions / Safety	FCC Class A, CE Class A, UL	FCC Class A, CE Class A	FCC Class A, CE Class A, UL, cUL	
	Stability	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)			

Gigabit					
Model	IGS-620TF	IGS-1020TF	IGS-1600T	IGS-1820TF	
Product Image					
Hardware	10/100/1000BASE-T	4	8	16	16
	10/100BASE-TX	-	-	-	-
	1000BASE-SX/LX	2 (100BASE-FX Compatible)	2	-	2 (100BASE-FX Compatible)
	Switch Fabric	12Gbps	20Gbps	32Gbps	36Gbps
	MAC Table	1k	8K	8K	8K
	Memory Buffer	-	-	-	-
Protocol	Auto-negotiation	●	●	●	●
	802.3x Flow Control	●	●	●	●
Power	Inputs	12~48VDC, Dual power input	12~48VDC, Dual power input	12~48VDC, Dual power input	12~48VDC, Dual power input
	Connector	6-pin removeable terminal block	6-pin removeable terminal block	6-pin removeable terminal block	6-pin removeable terminal block
	Consumption	12 watts	8.7 watts	16 watts	18 watts
Mechanical	Dimensions (W x D x H)	32 x 87.8 x 135 mm	56 x 87.8 x 135 mm	65 x 107 x 152 mm	65 x 107 x 152 mm
	Enclosure	IP30 metal	IP30 metal	IP40 metal	IP40 metal
	Mounting	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable	DIN-rail, Wall-mountable
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)	5% to 95%RH (non-condensing)
Regulatory	Emissions / Safety	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC Class A, CE Class A, UL	FCC Class A, CE Class A
	Stability	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)			

Industrial Media Converters

		Fast Ethernet			10G
Model		IFT-802T	IFT-802TS15	IFT-805AT	IXT-705AT
Product Image					
Copper	Copper Interface	1 x 10/100BASE-TX, RJ45, Auto-negotiation, Auto-MDI/MDI-X			1 x 10/1000/2500/5000/10G N BASE-T RJ45
	Optical Interface	100BASE-FX	100BASE-FX	100BASE-FX	10G BASE-FX
Fiber	Optical Connector	SC	SC	SFP	SFP+
	Optical Mode	Multi-mode	Single mode	Vary on module	Vary on module
	Max. Distance	2km	15km	Vary on module	Vary on module
	Optic Wavelength	1310nm	1310nm	Vary on module	Vary on module
	Fiber-optic Cable	50/125µm or 62.5/125µm multi-mode	9/125µm single mode	Vary on module	Vary on module
Mechanical	Dimensions (W x D x H)	32 x 87.8 135 mm	32 x 87.8 135 mm	32 x 87.8 135 mm	32 x 87.8 135 mm
	Weight	400g	400g	400g	400g
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail, wall-mountable		DIN-rail, wall-mountable	
Power	Inputs	Dual 12-48V DC	Dual 12-48V DC	Dual 12-48V DC	Dual 12-48V DC
	Connector	6-pin removable terminal block			6-pin removable terminal block
	PoE	-	-	-	-
	Consumption	4.6 watts max.	4.6 watts max.	4.6 watts max.	9 watts max.
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	5% to 95%RH (non-condensing)		5% to 95%RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)			
Management		-	-	-	-

Gigabit PoE						
Model		IGTP-815AT	IGTP-805AT	IGUP-805AT	IGUP-1205AT	IGUP-2205AT
Product Image						
Copper	Copper Interface	1 x 10/100/1000BASE-T, RJ45, Auto-negotiation, Auto-MDI/MDI-x		1 x 10/100/1000BASE-T, RJ45, Auto-negotiation, Auto-MDI/MDI-x		2 x 10/100/1000BASE-T, RJ45, Auto-negotiation, Auto-MDI/MDI-x
	Optical Interface	100/1000BASE-X	1000BASE-X	100/1000BASE-X	100/1000BASE-X	100/1000BASE-X
Fiber	Optical Connector	1 x SFP	SFP	1 x SFP	2 x 1000BASE-SX/LX/BX SFP Compatible with 100BASE-FX SFP	
	Optical Mode	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Max. Distance	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Optic Wavelength	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Fiber-optic Cable	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
Mechanical	Dimensions (W x D x H)	30 x 70 x 104 mm	32 x 87.8 x 135 mm	32 x 87 x 135 mm	55 x 85 x 135 mm	55 x 85 x 135 mm
	Weight	251g	500g	484g	612g	665g
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail kit and wall-mount ear	DIN-rail, wall-mountable	DIN-rail kit and wall-mount ear	DIN-rail kit and wall-mount ear	DIN-rail kit and wall-mount ear
Power	Inputs	DC 48-56V	DC 48-56V	DC 12-56V	Dual 12-56V DC	Dual 12-56V DC
	Connector	2-pin removable terminal block	6-pin removable terminal block	6-pin removable terminal block	6-pin removable terminal block	6-pin removable terminal block
	PoE	36 watts max.	30 watts max.	90 watts max.	90 watts max.	180 watts max.
	Consumption	43.12W	33W	DC 12V: 82W DC 48V: 98W	DC 12V: 82W DC 48V: 98W	DC 12V: 82W DC 48V: 98W
Environment	Operating Temperature	-40~75 degrees C			-40~75 degrees C	
	Operating Humidity	5%~90% RH (non-condensing)			5%~90% RH (non-condensing)	
Regulatory	Emissions	FCC Class A, CE Class A			FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)				
Management		-	-	-	-	-

Industrial Media Converters

		Gigabit				Managed		
Model	IGT-815AT	IGT-805AT	IGT-1205AT	IGT-2205AT	IGT-900-1T1S	IGT-900-2T2S	IGT-905A	
Product Image								
Copper	Copper Interface	1 x 10/100/1000BASE-T, RJ45, Auto-negotiation, Auto-MDI/MDI-X		2 x 10/100/1000BASE-T, RJ45, Auto-negotiation, Auto-MDI/MDI-X		1 x 10/100/1000BASE-T	2 x 10/100/1000BASE-T	1 x 10/100/1000BASE-T
Fiber	Optical Interface	100/1000BASE-X	100/1000BASE-X	100/1000/2500BASE-X		1 x 100/1000/2500BASE-X	2 x 100/1000/2500BASE-X	1 x 100/1000BASE-X
	Optical Connector	1 x SFP	SFP	SFP	SFP	SFP	SFP	SFP
	Optical Mode	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Max. Distance	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Optic Wavelength	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
Mechanical	Fiber-optic Cable	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module	Vary on module
	Dimensions (W x D x H)	30 x 70 x 104 mm	32 x 87.8 135 mm	32 x 87.8 135 mm	32 x 87.8 135 mm	32 x 87 x 135mm	32 x 87 x 135mm	32 x 87 x 135mm
	Weight	251g	458g	400g	400g	405g	405g	405g
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal	IP30 metal
Power	Mounting	DIN-rail kit and wall-mount ear	DIN-rail, wall-mountable			DIN-rail, wall-mountable		
	Inputs	DC 9~48V AC 24V	Dual 12~48V DC	Dual 12~48V DC	Dual 12~48V DC	Dual 9~48V DC	Dual 9~48V DC	Dual 12~48V DC
	Connector	2-pin Removable terminal Block	6-pin removable terminal block			6-pin removable terminal block		
	PoE	-	-	-	-	-	-	-
Environment	Consumption	2 watts max.	3.3 watts max.	7.5 watts max.	8.5 watts max.	7.7 watts max.	7.7 watts max.	7.7 watts max.
	Operating Temperature	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C		-30~75 degrees C
Regulatory	Operating Humidity	5% to 95%RH (non-condensing)				5% to 95%RH (non-condensing)		
	Emissions	FCC Class A, CE Class A		FCC Class A, CE Class A		FCC Class A, CE Class A		
Management	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)						
		-	-	-	-	WEB, SNMPv1,v2c,v3, RMON, 802.1Q VLAN, QinQ, Port Backup, LFP, ERPS		WEB,SNMPv1,v2c, RMON, 802.1Q VLAN, QinQ

Industrial Serial over Ethernet Converters

		Industrial Serial over Ethernet Converters			
Model	ICS-2200T	ICS-2400T	ICS-2100T/ICS-2105AT	ICS-2102T/ICS-2102TS	
Product Image					
Serial Port	Interface	2 x RS232/RS422/RS485	4 x RS232/RS422/RS485	1 x RS232/422/485	1 x RS232/422/485
	Connector	DB9	DB9	1 x DB9 for RS232 1 x 4-pin terminal block for RS422/485	
	Baud Rate (Data Rate)	100bps to 921Kbps	100bps to 921Kbps	50bps to 921Kbps	50bps to 921Kbps
	Data Bits	5, 6, 7, 8	5, 6, 7, 8	5,6,7,8	5,6,7,8
	Stop Bits	1, 2	1, 2	1,1.5,2	1,1.5,2
	Flow Control	None, RTS/CTS, Xon/Xoff	None, RTS/CTS, Xon/Xoff	None, RTS/CTS, Xon/Xoff	None, RTS/CTS, Xon/Xoff
Fast Ethernet Port	Standard	10/100BASE-TX	10/100BASE-TX	ICS-2100/ICS-2100T: 10/100BASE-TX ICS-2105A/ICS-2105AT: 100BASE-FX	100BASE-FX
	Connector	2 x RJ45	2 x RJ45	ICS-2100T: RJ45 ICS-2105AT: SFP	Duplex SC
	Optical Wavelength	-	-	ICS-2105AT: Vary on module	1310nm
	Max. Distance	100m	100m	ICS-2100/ICS-2100T: 100m ICS-2105A/ICS-2105AT: May vary on module	ICS-2102T: 2km ICS-2102TS: 30km
Power	Protection	Built-in 1.5KV magnetic isolation	Built-in 1.5KV magnetic isolation	6KV ESD	6KV ESD
	Power Supply	Dual 12~48V DC, 6-pin removable terminal block		Dual 9~48V DC or 24V AC, 6-pin removable terminal block	
Mechanical	Power Consumption	10.1 watts	10.1 watts	5 watts max.	5 watts max.
	Dimensions (W x D x H)	32 x 87.8 x 135 mm	56 x 87 x 135 mm	32 x 87 x 135 mm	32 x 87 x 135 mm
	Enclosure	IP30 metal	IP40 metal	IP30 metal	IP30 metal
Environment	Mounting	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable	DIN-rail, wall-mountable
	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
Regulatory	Operating Humidity	10% to 90%RH (non-condensing)	10% to 90%RH (non-condensing)	10% to 90%RH (non-condensing)	
	Emissions	FCC Class A, CE Class A	FCC Class A, CE Class A	FCC, CE	FCC, CE
Management	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration)			
	Interface	Web management, VCOM	Web management, VCOM	IPv4/IPv6 Web, telnet and SNMP management	
	Operation Mode	Virtual COM port, TCP server, UDP server, UDP client, pair connection		Virtual COM port, TCP server, UDP server, UDP client, pair connection, RFC2217, Telnet server, Modbus converter	

Industrial PoE Injectors, Splitters, Converters

		802.3at PoE+ Injectors				802.3bt PoE++ Injector		
Model		IPOE-162	IPOE-260/ IPOE-260-12V	IPOE-171-60W	IPOE-171-95W	IPOE-270/ IPOE-270-12V	IPOE-470/ IPOE-470-12V	IPOE-175
Product Image								
Hardware	RJ45 Data Input Port	1 x RJ45	2 x RJ45	1 x RJ45	1 x RJ45	2 x RJ45	4 x RJ45	1 x RJ45
	RJ45 Data + Power Output Port	1 x RJ45	2 x RJ45	1 x RJ45	1 x RJ45	2 x RJ45	4 x RJ45	1 x RJ45
	Data Rate	10/100/1000Mbps		10/100/1000Mbps		10/100/1000Mbps		10/100/1000Mbps
PoE Spec.	PoE Standard	802.3af/802.3at	802.3at	Ultra PoE (802.3at Compliant)		802.3bt Type-4 Backward compatible with 802.3at		802.3bt Type-3
	PSE Type	Mid-span	Mid-span	Both Mid-span and End-span		End-span + Mid-span		
	Power Pin Assignment	4/5(+), 7/8(-)	4/5(+), 7/8(-)	1/2(-), 3/6(+), 4/5(+), 7/8(-)		1/2(-), 3/6(+), 4/5(-), 7/8(+)		
	PoE Port	1	2	1	1	2	4	1
	PoE Power Output	56V DC	48-56V DC/54V DC	52-56V DC	54V DC	48-56V DC/54V DC		55V DC
	PoE Ability	30 watts	60 watts budget	60 watts	95 watts	180 watts budget	240 watts budget	60 watts
Physical	Dimensions (W x D x H)	32 x 87 x 135mm	30 x 70 x 104mm	32 x 87 x 135mm		41 x 70 x 115mm	56 x 87 x 135mm	150 x 72 x 44mm
	Power Supply	External	External	External	External	External	External	External
	Power Requirements	Dual 24-48V DC, 24V AC	Dual 48-56V DC/ Dual 12-56V DC	Dual 48-56V DC	Dual 12-48V DC	Dual 48-56V DC/ Dual 12-56V DC		Dual 24-56V DC
	Operating Temperature	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C		
Regulatory	EMI/Safety		FCC Class A, CE		FCC Class A, CE		FCC Class A, CE	

Industrial PoE Injectors, Splitters, Converters

		802.3at PoE+/802.3bt PoE++ Splitters		
Model		IPOE-162S	IPOE-173S	IPOE-175S
Product Image				
Hardware	Data + Power Input Port	1 x RJ45	1 x RJ45	1 x RJ45
	Data Output Port	1 x RJ45	1 x RJ45	1 x RJ45
	DC Output Voltage	12V/24V DC, max. 2A	10/100/1000Mbps	10/100/1000Mbps
	DIP Switch	Adjustable 12V/24V DC	12V/24V DC, max. 5A	12V DC, max. 5A
	Data Rate	10/100/1000Mbps	10/100/1000Mbps	10/100/1000Mbps
PoE Spec.	PoE Standard	802.3af/802.3at	802.3bt Type-4 PD	802.3bt Type-3 PD
	PD Type	Both Mid-span and End-span		
Physical	PoE Power Input	52-56V DC	52-56V DC	52-56V DC
	Dimensions (W x D x H)	32 x 87 x 135mm	32 x 87 x 135mm	150 x 72 x 44mm
Regulatory	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	EMI/Safety	FCC Class A, CE	FCC Class A, CE	FCC Class A, CE

		PoE Extender		PoE Tester
Model		IPOE-E302	IPOE-E174	POE TESTER+
Product Image				
Hardware	Data + Power Input Port	1 x RJ45	1 x RJ45	1 x RJ45
	Data Output Port	2 x RJ45	4 x RJ45	-
	DC Output Voltage	PoE 44-57V DC		
	DIP Switch	-	-	-
	Data Rate	10/100/1000Mbps	10/100/1000Mbps	10/100/1000Mbps
PoE Spec.	PoE Standard	802.3bt Type-4 PD	802.3bt Type-4 PD	802.3af/802.3at/802.3bt
	PD Type	Both Mid-span and End-span		
	PoE Power Input	51-56V DC	44-56V DC	36-57V DC
Physical	Dimensions (W x D x H)	150 x 72 x 44mm	56 x 87.8 x 135mm	70 x 23 x 22mm
	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-10~60 degrees C
Regulatory	EMI/Safety	FCC Class A, CE	FCC Class A, CE	CE compliance

Industrial Ethernet Extenders

		DIN-rail	
Model		IVC-234GT	
Product Image			
Copper	Copper Interface	4 x 10/100/1000BASE-T	
	Coaxial	1 BNC, female connector	
	UTP	1 RJ11, female connector	
Extended Port	Max. Performance (Download/Upload)	<ul style="list-style-type: none"> Coaxial Cable: Up to 200/95Mbps@200m UTP: Up to 200/100Mbps@200m 	
	Max. Distance	<ul style="list-style-type: none"> Coaxial Cable: Up to 1.2km UTP: Up to 1.2km 	
Mechanical	Cabling	<ul style="list-style-type: none"> Coaxial Cable: 50ohm, RG58A/U, RG58/U75ohm, RG6 Twisted-pair telephone wires (AWG24 or better) 	
	Dimensions (W x D x H)	32 x 87.8 x 135 mm	
	Weight	631g	
Power	Enclosure	IP30 metal	
	Mounting	DIN-rail, wall-mountable	
	Inputs	Dual 12-48V DC	
Environment	Connector	6-pin removable terminal block	
	Consumption	6.64 watts max.	
Regulatory	Operating Temperature	-40~75 degrees C	
	Operating Humidity	5% to 95%RH (non-condensing)	
Functionality	Emissions	FCC Class A, CE Class A	
	Stability	IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)	
		Master/Slave mode select, selectable BNC and RJ11 mode, selectable target band plan, selectable target SNR mode	

Industrial Gateways

Industrial Modbus Gateway

Model IMG-2100T/IMG-2105AT IMG-2200T IMG-2400T

Product Image



Serial Port	Interface	1 x RS232/422/485	2 x RS232/422/485	4 x RS232/422/485
	Connector	1 x DB9 for RS232 1 x 4-pin terminal block for RS422/485	2 x DB9	4 x DB9
	Baud Rate	50bps to 921kbps		
	Priority Type	None, Odd, Even, Space, Mark		
	Isolation	-	2KV	2KV
	Multi-master and Multi-drop	Master mode: 32 TCP slaves Slave mode: 32 TCP masters		
	Operation Mode	Modbus RTU Master/ Modbus RTU Slave/ Modbus ASCII Master/ Modbus ASCII Slave		
LAN Port	Standard	IMG-2100T/IMG-2200T/IMG-2400T: 10/100BASE-TX IMG-2105AT/IMG-2102T/IMG-2102TS: 100BASE-FX		
	Connector	IMG-2100T: RJ45 IMG-2105AT: SFP	2 x RJ45	2 x RJ45
	Max. Distance	IMG-2100T: 100m IMG-2105AT: May vary on module	100m	100m
	Protection	6KV ESD	6KV ESD	6KV ESD
Power	Power Input	Dual DC9-48V or AC 24V	Dual DC 12-48V	Dual DC 12-48V
	Power Interface	Removable terminal block		
	Power Consumption	5 watts max.	5.4 watts max.	6.5 watts max.
Mechanical	Dimensions (W x D x H)	32 x 87 x 135 mm	32 x 87 x 135 mm	56 x 87 x 135 mm
	Enclosure	IP30 metal	IP30 metal	IP40 metal
	Installation	Wall-mountable, DIN-rail mounting		
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C
	Emissions	FCC, CE	FCC, CE	FCC, CE
Regulatory	Stability	IEC60068-2-32 (free fall), IEC60068-2-27 (shock), IEC60068-2-6 (vibration)		
	Interface	IPv4 Web, telnet and SNMP management		
Management	Utility	MBVCOM utility, PLANET Smart Discovery		

Vehicle Cellular Gateway

Model VCG-1500WG-LTE

Product Image



Hardware	10/100BASE-TX	4
	WAN	1
	Wi-Fi	802.11n, 2.4GHz
	GPS	-
	SIM Card Slot	1
Multi Band Support	TF Card Slot	2
	EU Model	FDD LTE B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800) TDD LTE B38/B40/B41(2600/2300/2500) WCDMA B1/B5/B8(2100/850/900) GSM/EDGE B3/B8 (1800/900)
	US Model	FDD LTE B2/B4/B12 (1900/AWS1700/700) WCDMA B2/B4/B5 (1900/AWS1700/850)
Power	LTE	20MHz bandwidth: 100Mbps (DL), 50Mbps (UL)
	Inputs	6-32V DC
	Connector	Standard 4-pin vehicle power jack
Mechanical	Consumption	3 watts
	Dimensions (W x D x H)	168 x 104 x 25 mm
	Enclosure	IP30 metal
Environment	Mounting	Mounting brackets for vehicles
	Operating Temperature	-25~65 degrees C
Regulatory	Operating Humidity	95% (non-condensing)
	Emissions	FCC Part 15 Class A, CE
Management	Stability	Static Route, VPN, DDNS, IP Filter, QoS
	Interface	Console, Web, telnet
Management	Software Utility	CMS
	Log	Syslog Log

Industrial Cellular Gateways

Model ICG-2515-NR ICG-2515W-NR ICG-2510W-LTE ICG-2510WG-LTE

Product Image



Hardware	LAN	4 10/100/1000BASE-T	4 10/100/1000BASE-T	5 10/100/1000BASE-T	
	WAN	1	1	1	
	WLAN	-	2.4GHz & 5GHz 802.11ax 1800Mbps	2.4G/5G	2.4G/5G
	DI & DO	2 DI & 2 DO	2 DI & 2 DO	2 DI & 1 DO	2 DI & 1 DO
	GPS	GNSS positioning		-	●
	COM Port	1*RS485	1*RS485	1*RS232/RS485	1*RS232/RS485
Multi Band Support	5G NR	n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n38/n40/n41/n48/n66/n71/n77/n78/n79		-	
	4G LTE	B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/ B32/B46/B66/B71		EU Model: B1/B3/B5/B7/B8/B20/B38/B40/B41 US Model: B2/B4/B5/B12	
	Data Transmission Throughput	Sub-6G: 2.4Gbps (DL) / 500Mbps (UL) LTE: 1Gbps (DL) / 200Mbps (UL)		1.4/3/5/10/15/20MHz bandwidth: 150Mbps (DL), 50Mbps (UL)	
Power	Inputs	9~54V DC	9~54V DC	9~36V DC	9~36V DC
	Connector	6 pin terminal block	6 pin terminal block	6 pin 3.5mm terminal block	6 pin 3.5mm terminal block
	Consumption	6 watts	10 watts	7 watts	7 watts
Mechanical	Dimensions (W x D x H)	50 x 135 x 135 mm	50 x 135 x 135 mm	115.7 x 133 x 45	115.7 x 133 x 45
	Enclosure	IP30 metal	IP30 metal	IP30 metal	IP30 metal
	Mounting	DIN-rail and wall-mountable	DIN-rail and wall-mountable	DIN rail	DIN rail
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C	-35~75degrees	-35~75degrees
	Operating Humidity	5 ~ 90% (non-condensing)	5 ~ 90% (non-condensing)	95%(non-condensing)	95%(non-condensing)
Regulatory	Emissions	FCC Class A, CE class A	FCC Class A, CE class A	FCC Part 15 Class A, CE	FCC Part 15 Class A, CE
	Stability	IEC60068-2-32(Free Fall), IEC60068-2-27(shock), IEC60068-2-6(Vibration)		Static Route, Open VPN, DDNS, TR069, IP Filter, SMTP	
Management	Interface	Web browser, TLS, PLANET Smart Discovery utility, NMS Controller, CloudViewer supported		Console, Web, telnet	
	SNMP	v1, v2c, v3		v1, v2c, v3 and trap	
	System Log	System Event Log		System Log and Remote Syslog	

Industrial Gigabit SFP Modules

Model	MGB-TSX	MGB-TLX	MGB-TSX2	MGB-TL40	MGB-TL80	MFB-TFX	MFB-TF20
Product Image							
PHY Type	1000BASE-SX	1000BASE-LX	1000BASE-SX	1000BASE-LX	1000BASE-LX	100BASE-FX	100BASE-FX
Fiber Type	Multi-mode	Single mode	Multi-mode	Single mode	Single mode	Multi-mode	Single mode
Connector	LC	LC	LC	LC	LC	LC	LC
Wavelength	850nm	1310nm	1310nm	1310nm	1550nm	1310nm	1310nm
Maximum Distance	220m & 550m	20km	2km	40km	80km	2km	20km
Operating Temperature	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C				

Fast Ethernet Transceivers (100BASE-BX, Single Fiber Bi-directional SFP)

Model	MFB-TSA	MFB-TSB	MFB-TFA20	MFB-TFB20	MFB-TFA40	MFB-TFB40
Product Image						
Speed (Mbps)	100	100	100	100	100	100
Connector Interface	WDM (LC)	WDM (LC)	WDM (LC)	WDM (LC)	WDM (LC)	WDM (LC)
Fiber Mode	Multi mode	Multi mode	Single mode	Single mode	Single mode	Single mode
Distance	2km	2km	20km	20km	40km	40km
Wavelength (TX)	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm
Wavelength (RX)	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm
Operating Temp.	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C	-40~75 degrees C

Gigabit Ethernet Transceivers (1000BASE-BX, Single Fiber Bi-directional SFP)

Model	MGB-TLA10	MGB-TLB10	MGB-TLA20	MGB-TLB20	MGB-TLA40	MGB-TLB40	MGB-TLA60	MGB-TLB60
Product Image								
Speed (Mbps)	1000	1000	1000	1000	1000	1000	1000	1000
Connector Interface	WDM (LC)	WDM (LC)	WDM (LC)	WDM (LC)				
Fiber Mode	Single mode		Single mode		Single mode		Single mode	
Distance	10km	10km	20km	20km	40km	40km	60km	60km
Wavelength (TX)	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm
Wavelength (RX)	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm	1550nm	1310nm
Operating Temp.	-40~75 degrees C		-40~75 degrees C		-40~75 degrees C		-40~75 degrees C	


Model	MGB-2GTSR	MGB-2GTLR2	MGB-2GTLR20	MGB-2GTLA20	MGB-2GTLB20
Product Image					
Speed (Mbps)	2500	2500	2500	2500	2500
Connector Interface	LC	LC	LC	WDM (LC)	WDM (LC)
Fiber Mode	Multi mode	Single mode	Single mode	Single mode	Single mode
Distance	300m	2km	20km	20km	20km
Wavelength (TX)	850nm	1310nm	1310nm	1310nm	1550nm
Wavelength (RX)	850nm	1310nm	1310nm	1550nm	1310nm
Operating Temp.	-40~45 degrees C	-40~45 degrees C	-40~45 degrees C	-40~45 degrees C	-40~45 degrees C

DIN-rail Power Supplies

Model		PWR-40-24	PWR-60-24	PWR-75-24	PWR-75-48	PWR-120-48	PWR-240-48	PWR-480-48	
Product Image									
Power Output	Budget	40 watts	60 watts	75 watts	75 watts	120 watts	240 watts	480 watts	
	DC Voltage	24V, 1.7A	24V, 2.5A	24V, 3.2A	48V, 1.6A	48V, 2.5A	48V, 5A	48V, 10A	
Power Input	Voltage	100-240V AC, 50/60Hz, 1.1A	100-240V AC, 50/60Hz, 1.8A	100-240V AC, 50/60Hz, 2.0A	100-240V 50/60Hz, 1.45A	100-240V 50/60Hz, 2.25A	100-240V 50/60Hz, 2.5A	100-240V 50/60Hz, 4.8A	
Mechanical	Dimensions (W x H x D)	40 x 90 x 100 mm	40 x 90 x 100 mm	55 x 125 x 100 mm	32 x 125 x 102 mm	65 x 125 x 100 mm	63 x 125 x 113 mm	85.5 x 125.2 x 128.5 mm	
	Weight	0.3kg	0.33kg	0.6kg	0.51kg	0.6kg	1kg	1.5kg	
	Installation	DIN-rail TS-35/7.5 or 15			DIN-rail TS/35/7.5 or 15			DIN-rail TS/35/7.5 or 15	
Environment	Operating Temperature	-20~70 degrees C			-20~70 degrees C			-20~70 degrees C	
	Storage Temperature	-40~85 degrees C			-40~85 degrees C			-40~85 degrees C	
	Operating Humidity	20~90%	20~90%	20~90%	20~95%	20~95%	20~95%	20~95%	
	Storage Humidity	10~95% (non-condensing)			10~95% (non-condensing)			10~95% (non-condensing)	
Safety & Function	UL508, ul60950-1, TUV EN60950-1 approved, NEC class2/LPS compliant			UL508, UL60950-1, TUV EN6095-1 approved					

Industrial EtherCAT Slave I/O Modules

EtherCAT Slave			
Model	IECS-1116-DI	IECS-1116-DO	
Product Image			
Hardware	10/100/1000BASE-T	2 one IN, one OUT	2 one IN, one OUT
	DI	16 Dry (Source), Wet (Sink/Source)	-
	DO	-	16 Open Collector (Sink) 700mA/Channel
Power	Inputs	9V~48VDC	9V~48VDC
	Connector	3-pin terminal block	3-pin terminal block
Mechanical	Dimensions (W x D x H)	135 x 86 x 32 mm	135 x 86 x 32 mm
	Mounting	DIN-rail, wall-mountable	DIN-rail, wall-mountable
Environment	Operating Temperature	-40~75 degrees C	-40~75 degrees C
	Operating Humidity	10~95% (non-condensing)	10~95% (non-condensing)
Protocol	EtherCAT		





PLANET Technology Corporation

11F., No 96, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: +886-2-2219-9518

Fax: +886-2-2219-9528

E-mail: sales@planet.com.tw

PLANET reserves the right to change specifications without prior notice. All brand names and trademarks are property of their respective owners.

© PLANET Technology Corporation DM-IE0122